# SAFETY DATA SHEET



Halocarbon R-113 (1,1,2-Trichlorotrifluoroethane)

## **Section 1. Identification**

**GHS** product identifier

: Halocarbon R-113 (1,1,2-Trichlorotrifluoroethane)

**Chemical name** 

: 1,1,2-trichlorotrifluoroethane

Other means of identification

: Ethane, 1,1,2-trichloro-1,2,2-trifluoro-; 1,1,2-Trichloro-1,2,2-trifluoroethane; 1,2,2-Trichlorotrifluoroethane; Algofrene 113; Genetron 113; Freon 113; Refrigerant 113;

Halocarbon 113; Chlorofluorocarbon-113; TTE; CFC-113

**Product type** 

: Liauid.

**Product use** 

: Synthetic/Analytical chemistry.

**Synonym** 

: Ethane, 1,1,2-trichloro-1,2,2-trifluoro-; 1,1,2-Trichloro-1,2,2-trifluoroethane;

1,2,2-Trichlorotrifluoroethane; Algofrene 113; Genetron 113; Freon 113; Refrigerant

113; Halocarbon 113; Chlorofluorocarbon-113; TTE; CFC-113

SDS#

Supplier's details

: Airgas USA, LLC and its affiliates 259 North Radnor-Chester Road

Suite 100

Radnor, PA 19087-5283

1-610-687-5253

24-hour telephone

: 1-866-734-3438

## Section 2. Hazards identification

**OSHA/HCS** status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : EYE IRRITATION - Category 2A

AQUATIC HAZARD (LONG-TERM) - Category 2 HAZARDOUS TO THE OZONE LAYER - Category 1

**GHS** label elements

**Hazard pictograms** 





Signal word

: Warning

**Hazard statements** 

: Causes serious eye irritation.

Toxic to aquatic life with long lasting effects.

Harms public health and the environment by destroying ozone in the upper atmosphere.

**Precautionary statements** 

General

: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

**Prevention** 

: Wear eye or face protection. Avoid release to the environment. Wash hands thoroughly after handling. Use and store only outdoors or in a well ventilated place.

Response

: Collect spillage. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

**Disposal** 

: Dispose of contents and container in accordance with all local, regional, national and international regulations. Refer to manufacturer or supplier for information on recovery or recycling.

Hazards not otherwise

classified

None known.

Date of issue/Date of revision Date of previous issue 1/11 : 3/25/2021 : 3/23/2016 Version : 0.02

## Section 3. Composition/information on ingredients

Substance/mixture

: Substance

**Chemical name** 

: 1.1.2-trichlorotrifluoroethane

Other means of identification

Ethane, 1,1,2-trichloro-1,2,2-trifluoro-; 1,1,2-Trichloro-1,2,2-trifluoroethane;

1,2,2-Trichlorotrifluoroethane; Algofrene 113; Genetron 113; Freon 113; Refrigerant 113;

Halocarbon 113; Chlorofluorocarbon-113; TTE; CFC-113

Product code : 001098

#### **CAS** number/other identifiers

**CAS number** : 76-13-1

Ingredient name	%	CAS number
1,1,2-Trichlorotrifluoroethane	100	76-13-1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### **Description of necessary first aid measures**

**Eye contact** 

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

**Inhalation** 

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Skin contact** 

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

## Most important symptoms/effects, acute and delayed

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.Skin contact : No known significant effects or critical hazards.

Frostbite : Try to warm up the frozen tissues and seek medical attention.

**Ingestion**: No known significant effects or critical hazards.

#### **Over-exposure signs/symptoms**

**Eye contact**: Adverse symptoms may include the following:, pain or irritation, watering, redness

Inhalation : No specific data.

Date of issue/Date of revision : 3/25/2021 Date of previous issue : 3/23/2016 Version : 0.02 2/11

## Section 4. First aid measures

: No specific data. **Skin contact** Ingestion : No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments** 

: No specific treatment.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### See toxicological information (Section 11)

## Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing

media

Unsuitable extinguishing media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal** decomposition products : Decomposition products may include the following materials: carbon dioxide carbon monoxide

: Use an extinguishing agent suitable for the surrounding fire.

halogenated compounds

carbonyl halides

**Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

## Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### Methods and materials for containment and cleaning up

Date of issue/Date of revision : 3/25/2021 Date of previous issue : 3/23/2016 Version : 0.02 3/11

## Section 6. Accidental release measures

### **Small spill**

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

## **Precautions for safe handling**

### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Avoid breathing vapor or mist. Avoid release to the environment. Refer to special instructions/safety data sheet. Avoid contact with eyes, skin and clothing. Do not ingest. Empty containers retain product residue and can be hazardous. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container.

## **Advice on general** occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits

Ingredient name	Exposure limits
1,1,2-Trichlorotrifluoroethane	ACGIH TLV (United States, 3/2019).  TWA: 1000 ppm 8 hours.  TWA: 7670 mg/m³ 8 hours.  STEL: 1250 ppm 15 minutes.  STEL: 9590 mg/m³ 15 minutes.  OSHA PEL 1989 (United States, 3/1989).  TWA: 1000 ppm 8 hours.  TWA: 7600 mg/m³ 8 hours.  STEL: 1250 ppm 15 minutes.  STEL: 9500 mg/m³ 15 minutes.  NIOSH REL (United States, 10/2016).  TWA: 1000 ppm 10 hours.  TWA: 7600 mg/m³ 10 hours.  STEL: 1250 ppm 15 minutes.  STEL: 9500 mg/m³ 15 minutes.  TWA: 7600 mg/m³ 15 minutes.  OSHA PEL (United States, 5/2018).  TWA: 1000 ppm 8 hours.  TWA: 7600 mg/m³ 8 hours.

Date of issue/Date of revision Date of previous issue : 3/25/2021 : 3/23/2016 Version : 0.02

# Section 8. Exposure controls/personal protection

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** 

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

**Skin protection** 

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

## **Appearance**

**Physical state** 

: Liquid. [COLORLESS TO WATER-WHITE LIQUID WITH AN ODOR LIKE CARBON TETRACHLORIDE (AT HIGH CONCENTRATIONS) [NOTE: A GAS ABOVE 118 F.]]

Color : Colorless. Clear.

Odor : Characteristic.

Odor threshold : Not available.

pH : Not available.

Melting point : -35°C (-31°F)

Boiling point : 47.7°C (117.9°F)

Critical temperature : 214.1°C (417.4°F)

Flash point : [Product does not sustain combustion.]

**Evaporation rate** : 21 (butyl acetate = 1)

Flammability (solid, gas) : Not available.

Lower and upper explosive : Not available.

(flammable) limits

**Vapor pressure** : @ 70°F (21.1°C) = 5.6 psia (38.6 kPa)

Vapor density : 6.5 (Air = 1) Specific Volume (ft  $^3$ /lb) : 0.6349

Date of issue/Date of revision : 3/25/2021 Date of previous issue : 3/23/2016 Version : 0.02 5/11

## Section 9. Physical and chemical properties

**Gas Density (lb/ft** <sup>3</sup>) : 1.575 **Relative density** : 1.56

**Solubility** : Not available.

**Solubility in water** : 0.2 g/l **Partition coefficient: n-** : 3.16

octanol/water

Auto-ignition temperature : 680°C (1256°F)

Decomposition temperature : Not available.

Viscosity : Not available.

Flow time (ISO 2431) : Not available.

Molecular weight : 187.37 g/mole

## Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**Hazardous polymerization**: Under normal conditions of storage and use, hazardous polymerization will not occur.

## **Section 11. Toxicological information**

## Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
1,1,2-Trichlorotrifluoroethane	LC50 Inhalation Gas. LC50 Inhalation Gas. LD50 Oral	Rat		1 hours 4 hours -

## **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
1,1,2-Trichlorotrifluoroethane	Skin - Mild irritant	Rabbit	-	24 hours 500	-
	Skin - Mild irritant	Rabbit	-	mg 500 mg	-

### **Sensitization**

Not available.

### **Mutagenicity**

Not available.

### **Carcinogenicity**

Not available.

Date of issue/Date of revision : 3/25/2021 Date of previous issue : 3/23/2016 Version : 0.02 6/11

# **Section 11. Toxicological information**

## **Reproductive toxicity**

Not available.

## **Teratogenicity**

Not available.

## **Specific target organ toxicity (single exposure)**

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

Information on the likely routes of exposure

: Routes of entry anticipated: Oral, Inhalation.

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:, pain or irritation, watering, redness

Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

## Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

**Long term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

### Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

## **Numerical measures of toxicity**

**Acute toxicity estimates** 

Date of issue/Date of revision : 3/25/2021 Date of previous issue : 3/23/2016 Version : 0.02 7/11

# **Section 11. Toxicological information**

Route	ATE value
	43000 mg/kg 38000 ppm

## **Section 12. Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
1,1,2-Trichlorotrifluoroethane	Acute LC50 6240 mg/l Marine water	Fish - Fundulus heteroclitus	96 hours

#### Persistence and degradability

Not available.

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
1,1,2-Trichlorotrifluoroethane	3.16	50.12	low

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

## Section 13. Disposal considerations

## **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	-				
	DOT	TDG	Mexico	IMDG	IATA
UN number	Not regulated.				
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)		-	-	-	-
Packing group	-	-	-	-	-

Date of issue/Date of revision : 3/25/2021 Date of previous issue : 3/23/2016 Version : 0.02 8/11

Halocarbon R-113 (1,1,2-Trichlorotrifluoroethane) **Section 14. Transport information** 

Environmental	No.	No.	No.	No.	No.
hazards					

<sup>&</sup>quot;Refer to CFR 49 (or authority having jurisdiction) to determine the information required for shipment of the product."

#### **Additional information**

**DOT Classification** : Reportable quantity 5000 lbs / 2270 kg [380.74 gal / 1441.3 L]. Package sizes

shipped in quantities less than the product reportable quantity are not subject to the RQ

(reportable quantity) transportation requirements.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

Transport in bulk according : Not available.

to IMO instruments

## Section 15. Regulatory information

U.S. Federal regulations : TSCA 8(a) CDR Exempt/Partial exemption: Not determined

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)** 

**Clean Air Act Section 602** 

**Class I Substances** 

**Clean Air Act Section 602** 

**Class II Substances** 

**DEA List I Chemicals** 

(Precursor Chemicals)

**DEA List II Chemicals** 

(Essential Chemicals)

: Not listed

: Not listed

: Not listed

: Listed

: Not listed

### **SARA 302/304**

## **Composition/information on ingredients**

No products were found.

**SARA 304 RQ** : Not applicable.

**SARA 311/312** 

Classification : Refer to Section 2: Hazards Identification of this SDS for classification of substance.

<u>SARA 313</u>

	Product name	CAS number	%
Form R - Reporting requirements	1,1,2-trichlorotrifluoroethane	76-13-1	100
Supplier notification	1,1,2-trichlorotrifluoroethane	76-13-1	100

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

## **State regulations**

**Massachusetts** : This material is listed. : This material is listed. **New York** This material is listed. **New Jersey Pennsylvania** : This material is listed.

California Prop. 65

Date of issue/Date of revision : 3/25/2021 : 3/23/2016 Version : 0.02 9/11 Date of previous issue

## Section 15. Regulatory information

This product does not require a Safe Harbor warning under California Prop. 65.

#### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### **Montreal Protocol**

Ingredient name	Status
CFC 113	Annex A, Group I

### Stockholm Convention on Persistent Organic Pollutants

Not listed.

### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

### **Inventory list**

Australia : This material is listed or exempted.

Canada : This material is listed or exempted.

China : This material is listed or exempted.

Europe : This material is listed or exempted.

Japan : Japan inventory (ENCS): This material is listed or exempted.

Japan inventory (ISHL): Not determined.

New Zealand : This material is listed or exempted.
 Philippines : This material is listed or exempted.
 Republic of Korea : This material is listed or exempted.
 Taiwan : This material is listed or exempted.

Thailand : Not determined.

Turkey : Not determined.

United States : This material is active or exempted.

Viet Nam : Not determined.

## **Section 16. Other information**

### **Hazardous Material Information System (U.S.A.)**



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

**National Fire Protection Association (U.S.A.)** 

Date of issue/Date of revision : 3/25/2021 Date of previous issue : 3/23/2016 Version : 0.02 10/11

## **Section 16. Other information**



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

### Procedure used to derive the classification

Classification	Justification
AQUATIC HAZARD (LONG-TERM) - Category 2	Expert judgment Expert judgment Expert judgment

#### **History**

Date of printing : 3/25/2021

Date of issue/Date of : 3/25/2021

revision

Date of previous issue : 3/23/2016 Version : 0.02

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

References : Not available.

Other special considerations

: WARNING: Contains (Halocarbon R-113 (1,1,2-Trichlorotrifluoroethane), a substance which harms the public health and environment by destroying ozone in the upper atmosphere.

## **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision : 3/25/2021 Date of previous issue : 3/23/2016 Version : 0.02 11/11